

**CI3042GS-POE**

L2 Industrial PoE Managed Ethernet Switch

4GE + 2SFP



-40 - 80°C



8KV surge protection



ERPS <20ms



IP40 Protection

Brief Views

CI3042GS-POE an hardened 6-port Industrial Ethernet Switch, provides non-blocking wire-speed performance in harsh industrial environment. It provides 4-port 10/100/1000BASE-TX RJ45 +2G SFP delivered in an IP40 rugged, strong case with redundant power system. Its slim case is suitable for such applications as surveillance system deployments, control management and wireless service in climatically demanding environments with wide temperature range from -40°C to 80°C.

电源1指示灯



1xconsole

Functional Features

- 4*10/100/1000M RJ45 Auto MDI/MDIX
- 2*100/1000M SFP ports ;
- Support IEEE802.3af/at;
- Support LACP protocol;
- Support LLDP protocol;
- Support IGMP Snooping ,IGMP V1/V2/V3 ;
- Support STP/RSTP/MSTP, support ERPS (self-healing time <20ms) ;
- Support QoS (IEEE 802.1p/1Q) and TOS/Diffserv to increase network stability ;
- Support ACL access control list ;
- Support WEB, SNMP management mode ;
- Support power supply, port, abnormal state relay output.

Hardware

- **Downlink ports**
 - 4*10/100/1000BASE-T RJ45 ports
- **Uplink ports**
 - 2*SFP
- **Console port**
 - 1 pcs
- **Switching capability**
 - 45.6Gbps
- **Packets switching capability**
 - 8.92Mpps
- **Switching method**
 - Storage forwarding
- **LED light**
 - Power,system
- **Environment parameters**
 - Work temperature : -40° to 80°C
 - Storage temperature : -40 to 85°C
 - Work humidity : 5% to 95%
 - Storage humidity : 5% to 95%
- **IP class**
 - IP40 aluminum housing
- **MAC table size**
 - 8K
- **FAN**
 - Fanless,natural cold
- **MTBF**
 - >300,000hours
- **Power**
 - 48 to 57V DC redundant power
- **Power consumption**
 - <10W
- **Dimension (W*D*Hmm)**
 - 143.7 x 103 x 44.2mm
- **Weight**
 - Product Weight: 0.65KG
 - Packing Weight: 0.75KG
- **Certification**
 - CE FCC ROHS compliance
- **Installation**
 - DIN rail

● EMC

- IEC61000-4-2 (ESD): $\pm 8\text{kV}$ (contact), $\pm 12\text{kV}$ (air)
- IEC61000-4-3 (RS): 10V/m (80~1000MHz)
- IEC61000-4-4 (EFT): Power Port: $\pm 4\text{kV}$; Data Port: $\pm 2\text{kV}$
- IEC61000-4-5 (Surge): Power Port: $\pm 2\text{kV/DM}$, $\pm 4\text{kV/CM}$; Data Port: $\pm 2\text{kV}$
- IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz)
- IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)

● PoE

- IEEE802.3af/ IEEE802.3at
- 1-4 ports support PoE
- Output Voltage: DC48V
- Max. 15.4 watts (IEEE 802.3af)
- Max. 30 watts (IEEE 802.3at)
- PoE port Auto detect AF/AT devices
- Power Pin Assignment:1/2+;3/6-
- End-span(Mid-span optional)

Software

● Jumbo Frames

- 9600bytes

● VLAN

- Port based VLAN
- IEEE 802.1Q VLAN
- Max.4094 VLANs
- Support GVRP protocol
- Support Access,Trunk,Hybrid

● QoS

- IEEE 802.1p/1Q
- TOS/ Diffserv

● LACP

- Support Link Aggregation Control Protocol

● LLDP

- Support Link Layer Discovery Protocol

● Multicast

- IGMP v1/v2/v3
- IGMP snooping

● Security feature

- Support ACL
- Support 802.1x
- Support user classification management
- Support mac address binding
- Ring protect protocol
- Support STP/RSTP/MSTP
- Support ERPS (self-healing time <20ms)

● Flow control

- Support 802.3x full duplex flow control
- Support network storm suppression

● Monitoring maintenance

- Support port mirroring
- Support interface status monitoring
- Support log management

- **Storm control**

- Broadcast/Multicast/Unknown Unicast storm control

- **SNMP**

- SNMP V1,V2,V3

- **DHCP Snooping**

- Prevent illegal DHCP server

- **Alarm function**

- Support power supply, port, abnormal state relay output

- **Network management**

- Support SSH/Telnet

- CLI

- SNMP

- WEB

(IP:192.168.10.12 ,username/password: admin/admin)